

ANL2101S-W

Bluetooth Cylinder Smart Lock



Functions

- 3-way opening: Mifare Card, password and mechanical key
- Privacy password: xxx+password+xxx, preventing password to be seen by others
- Passage Mode and Non-disturbance Mode optional
- Auto lock when come across a consecutive invalid passwords or cards
- Low Voltage alarm($\leq 4.5V$)
- Huge storage: 50 cards, 50 passwords
- Emergency power supply outside
- Two colors optional
- Zinc alloy material

Card	
Card Type	Mifare 1
Card Features	Contactless, High Security, All-In-One Possible
Sensor Distance	< 20mm
Sensor Time	< 0.5s
Storage Capacity	50
Password	
Keyboard Type	All-Touch Keyboard
Password Length	6-12 bits
Storage Capacity	50
Battery	
Working Voltage	6V, AA Alkaline Battery (4pcs)
Battery Life	About 1 Year (10 Units/D)
Low Battery Warning	< DC4.5V
Emergency Power Supply	9V Battery
Structure	
Door Thickness	35-60mm
Backset	60/70mm
Material	Zinc Alloy
General	
Working Temperature	-20°C~+55°C
Relative Humidity	10%~93%
Salt Spray Test	≥200h
Lock Case Test	≥100000 times
Package Size	315*230*160(mm)
Gross Weight	3.3Kg
Restore Default	Support
Reset	Support
Built-in Buzzer	Support

Dimensions (mm)

