

# NVR5432-4KS2

32 Channel 1.5U 4HDDs 4K & H.265 Pro Network Video Recorder



## Functions

### Perimeter Protection by Camera

Automatically filters out false alarms caused by animals, rustling leaves, bright lights, and more. Enables system to act secondary recognition for the targets. Improving alarm accuracy.

### Face Recognition by Camera

Face recognition technology extracts the features of captured faces and compares them with that in face database to recognize the person identity

### SMD Plus by Camera

With intelligent algorithm, smart motion detection technology can categorize the targets that trigger motion detection and filter the motion detection alarm triggered by non-concerned targets to realize effective and accurate alarm.

### Video Metadata by Camera

With deep learning algorithm, Dahua video metadata technology can detect, track, capture vehicle, non-motor vehicle and people, and select the best images, and extract attributes.

### ANPR by Camera

With deep learning algorithm, ANPR technology can recognize the number plate information of vehicles in the image with ANPR cameras. Support block/allowlist mode, searching target vehicles from recorded video.

### Fisheye Dewarping

Fisheye dewarping solves the problem of distortion in the circular panoramic view. The NVR offers various dewarping modes for different installations and configurations that enhance the video, in both live or playback modes. Each dewarping mode offers options to adjust each scene.

### People Counting by Camera

With deep learning algorithm, People Counting technology can track and process moving human body targets to realize the accurate statistics of enter No., leave No., and In Area No. Working with management platform, it outputs yearly/monthly/weekly/daily reports to meet your requirements.

### Stereo Analysis by Camera

With deep learning algorithm and scene 3-dimensional information, stereo analysis technology can recognize people's behaviors, such as fall detection, violence detection, strand detection, and space exception, and then generates alarm signals and triggers linkage.

### DMSS

The DMSS app is available on the iOS App Store and Google Play. It makes surveillance easy and simple, allowing you to remotely access back-end devices, view live video, receive event push notifications, and search for recorded videos from an iPhone, iPad, or Android phone at anytime from virtually anywhere.

<b>System</b>	
Main Processor	Industrial Embedded Micro-Processor
Operating System	Embedded Linux
Operation Interface	Web; local GUI
<b>Perimeter Protection by Camera</b>	
Performance	20 Channels
AI Search	Search for Pictures by Channel, Time and Event Type
<b>Face Recognition by Camera</b>	
Performance	14 Channels
Face Attributes	6 Attributes: Gender; Age; Glasses; Expression; Mouth Mask; Beard
AI Search	Search for Pictures by Channel, Time and Face Attributes
<b>SMD Plus by Camera</b>	
Performance	32 Channels
AI Search	Search by Target Classification (Human, Vehicle)
<b>Video Metadata by Camera</b>	
Performance	16 Channels
Human Body	Top; Top Color; Bottom; Bottom Color; Hat; Bag; Gender; Age; Umbrella
Vehicle	Plate No.; Type; Color; Vehicle Type; Logo; Plate Color; Ornament; Calling; Seatbelt; Region
Non-Motor Vehicle	Type; Color; Number of Passengers; Helmet
AI Search	Supports Searching for Target Video by Metadata
<b>ANPR by Camera</b>	
Performance	4 Channels
<b>Stereo Analysis by Camera</b>	
Performance	16 Channels
AI Search	Search by Target Classification (Fall Detection; People Approach Detection; People No. Exception Detection; People Staying Detection; Violence Detection)
<b>Video</b>	
Access Channel	32
Network Bandwidth	320 Mbps for Access, 320 Mbps for Storage and 320 Mbps for Forwarding
Resolution	12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080p, 1.3MP, 720p, D1, and More
Decoding Capability	16-Channel@1080P (30 fps)
Video Output	HDMI1: 3840 × 2160; 1920 × 1080; 1280 × 1024; 1280 × 720
	VGA1: 1920 × 1080; 1280 × 1024; 1280 × 720
	HDMI2/VGA2: 1920 × 1080
	VGA1/HDMI1 Homologous Output, VGA2/HDMI2 Homologous Output, and VGA1/HDMI1 and VGA2/HDMI2 Supports Heterogeneous Output

Video	
Multi-Screen Display	1st Screen: 1/4/8/9/16/25/36 2nd Screen: 1/4/8/9/16
Third Party Camera Access	Panasonic, Sony, Samsung, Axis, Pelco, Arecont, ONVIF, Canon and More
Compression	
Video	Smart H.265+; Smart H.264+; H.265; H.264; MJPEG
Audio	PCM; G.711A; G.711U; G.726
Network	
Network Protocol	HTTP; HTTPS; TCP/IP; IPv4/IPv6; UPnP; SNMP; RTSP; UDP; SMTP; NTP; DHCP; DNS; IP Filter; PPPoE; DDNS; FTP; Alarm Server; IP Search (Supports Dahua IP Camera, DVR, NVS, and More.) ; P2P
Mobile Phone Access	Android; iOS
Interoperability	ONVIF (Profile T/S/G); CGI; SDK
Browser	Chrome; IE9 or Later; Firefox
Record Playback	
Multi-Channel Playback	1/4/9/16
Record Mode	Manual; Schedule (General; MD; Alarm; MD & Alarm; Intelligent; POS)
Storage Method	Local HDD and Network
Backup	USB Device
Playback Function	1. Play; Pause; Stop; Fast Forward; Fast Backward; Rewind; Play by Frame 2. Full Screen; Backup (Cut/File); Partially Enlarge; Audio On/Off
Storage	
Disk Group	Yes
Alarm	
General Alarm	Motion Detection; Privacy Masking; Video Loss; Local Alarm; PIR Alarm; IPC Alarm
Anomaly Alarm	Camera Offline; Storage Error; Full Storage; IP Conflict; MAC Conflict; Login Lock; Network Security Anomaly
Intelligent Alarm	Perimeter Protection; Face Detection; Face Recognition; SMD; Video Metadata (Human; Motor-Vehicle; Non-Motor Vehicle) ; ANPR; People Counting; Stereo Analysis; Crowd Distribution; Heat Map
Alarm Linkage	Record; Snapshot; IPC External Alarm Output; Buzzer; Log; Preset; Email
External Port	
Audio Input	1 Channel, RCA Connector
Audio Output	2 Channels, RCA Connector, Which Supports Voice Intercom Output
HDD	4 SATA III ports, Up to 10 TB for a Single HDD. The maximum HDD Capacity Varies with Environment Temperature.
Alarm Input	16 Channels
Alarm Output	6 Channels
eSATA	1 eSATA
RS-232	1 Channel, Used to Debug and Pass Through Serial Data
RS-485	1 Channel, Used to Control PTZ, and It Supports Multiple Protocols
USB	2 Front USB 2.0 Ports, 2 Rear USB 3.0 Ports
HDMI	2
VGA	2
Network	2 RJ-45 10/100/1000 Mbps Self-Adaptive Ethernet Ports
General Parameter	
Power Supply	Single, 100V–240V AC, 50 Hz–60 Hz
Power Consumption	< 16.7W (Without HDD)
Net Weight	4.3 kg (9.5 lb) (Without HDD)
Gross Weight	7 kg (15.4 lb) (Without HDD)
Product Dimensions	440 mm × 412.2 mm × 76.0 mm (17.3" × 16.2" × 3.0")

# NVR5432-4KS2

General Parameter	
Package Dimensions	522 mm × 492 mm × 200 mm (20.6" × 19.4" × 7.9")
Operating Temperature	-10°C to +55°C (+14°F to +131°F)
Storage Temperature	0°C to +40°C (+32°F to +104°F)
Operating Humidity	10%–93% (RH)
Storage Humidity	30%–85% (RH)
Operating Altitude	3,000 m (9,843 ft)

## Dimensions (mm)

